



Using S7-LAN with an ALF as a WLAN Router


9352-ALF




1 Connect the 24V power source and the computer to configure




3 Configure your IP address and subnet mask



5 Connect the S7-LAN with a patch cable
Your S7-LAN is now available from every WLAN participants



2 Select „AP-Router“ on menu „Easy Setup“



4 Now configure your networkname and encryption

Our recommended encryption is WPA2




6 Installing TIC driver
TIC driver available on www.tpa-partner.de


Integrate a S7-LAN in a available WLAN with an ALF



1 Connect the 24V power source and the computer to configure



2 Select „Client Bridge“ on menu „Easy Setup“



3 Press „Site Survey“ to search every WLAN and select your WLAN



4 Select your WLAN and enter your passwort. Press „Done“ to confirm




5 Connect the S7-LAN with a patch cable
Every network has to be in the same IP area
Your Module is now integrated




6 Installing TIC driver

TIC driver available on
www.tpa-partner.de


Integrate a S5-LAN++ in a available WLAN with an ALF




1 Connect the 24V power source and the computer to configure



2 Select „Client Bridge“ on menu „Easy Setup“



3 Press „Site Survey“ to search every WLAN and select your WLAN



4 Select your WLAN and enter your password. Press „Done“ to confirm




5 Connect the S5-LAN++ with a patch cable
Every network has to be in the same IP area
Your Module is now integrated




6 Installation:
- S5-Patch for original Step5
- PLCVCOM (virtual COM-Port)
Tools available on
www.tpa-partner.de


Using S5-LAN++ with an ALF as a WLAN Router




1 Connect the 24V power source and the computer to configure



2 Select „AP-Router“ on menu „Easy Setup“



3 Configure your IP address and subnet mask



4 Now configure your **networkname** and **encryption**

Our recommended encryption is WPA2



5 Connect the S5-LAN++ with a patch cable
Your S5-LAN++ will get an IP from the DHCP server and is now available from every WLAN participants



6 Installation:
- S5-Patch for original Step5
- PLCVCOM (virtual COM-Port)
Tools available on
www.tpa-partner.de

Under the web-address <https://www.process-informatik.de> are product specific documentations or software-driver/-tools available to download.
If you have questions or suggestions about the product, please don't hesitate to contact us.

Process-Informatik Entwicklungsgesellschaft mbH

Im Gewerbegebiet 1

DE-73116 Wäschchenbeuren

+49 (0) 7172-92666-0

info@process-informatik.de

<https://www.process-informatik.de>

Copyright by PI - 2026

Menutree Website:


- + Products / docu / downloads
- + Hardware
 - + Programming devices
 - + Programming adapter S7
 - + WLAN/WIFI
 - + Profinet PLCs / Ethernet-CPs
 - + ALF-Devices
 - + ALF

QR-Code Website:



Please make sure to update your drivers before using our products.


WinTELEPROF-software = software-PG-TELE



You're using the devices of the Tele-Network-family and don't want to have a device standing on the table? No problem. Install the WinTELEPROF-software on your PC and after link connection access to your Step5/7-programming software (also Siemens) via a virtual Com-Port.


At Step5 the Step5-software is going to be patched, then working with the virtual Com-Port will be also possible.

Remote maintenance of centralized PLC-devices




You have many PLC and you want to programm them central on one place? No problem, you have to connect them all to the KOR/MUX-Tele-Switch, connect it with the TP-II and after telephone connect you will be able with the PD-bus-selection of your Step5-software to go ONLINE. Of course the MOR/MUX-Tele-Switch is cascadable, so you can connect up to 30 PLCs to the devices.

Longer distances for L1-Bus



You need for your L1-Bus higher distance like the possible 1200m? You have strong disturbance on your L1-Bus? You need a serial line for higher distances and this galvanic decoupled? No problem, all this points are solved through the LWL-adapter. They are available for artificial and optical fibre, for L1-Bus and RS232.

Insensible communication with the S5-PLC




Safe communication with the S5-PLC in an environment of radiant-converters and motor-controls. Electrostatic-charging is also a KO-criterion for operation of interface-cable, a discharge and the interface-product is damaged or even defective.

PG-UNI-II is prepared for this, with its full-metal-cast-housing and ESD-proof components it offers the best protection against such influences. The shielding of the cable connected to the metal-housing is the solution. Of course, the cable can be extended to a TTY-distance of up to 300m, using adapter for PG-UNI-cables is also possible.

Sensor-networking 4.0



Data backup S5-PLC on FTP-server via dig. IO



Via digital input triggered DB-backup/-restore without additional PC via PG-socket and Ethernet to FTP-server