




Using S7-LAN with an ALF as a WLAN Router




- 1 Connect the 24V power source and the computer to configure



- 2 Select „AP-Router“ on menu „Easy Setup“



- 3 Configure your IP address and subnet mask



- 4 Now configure your networkname and encryption
Our recommended encryption is WPA2




- 5 Connect the S7-LAN with a patch cable
Your S7-LAN is now available from every WLAN participants




- 6 Installing TIC driver
TIC driver available on www.tpa-partner.de


Integrate a S7-LAN in a available WLAN with an ALF




- 1 Connect the 24V power source and the computer to configure



- 2 Select „Client Bridge“ on menu „Easy Setup“



- 3 Press „Site Survey“ to search every WLAN and select your WLAN



- 4 Select your WLAN and enter your password. Press „Done“ to confirm




- 5 Connect the S7-LAN with a patch cable
Every network has to be in the same IP area
Your Module is now integrated




- 6 Installing TIC driver
TIC driver available on www.tpa-partner.de


Integrate a S5-LAN++ in a available WLAN with an ALF




1 Connect the 24V power source and the computer to configure



2 Select „Client Bridge“ on menu „Easy Setup“



3 Press „Site Survey“ to search every WLAN and select your WLAN



4 Select your WLAN and enter your password. Press „Done“ to confirm




5 Connect the S5-LAN++ with a patch cable
Every network has to be in the same IP area
Your Module is now integrated




6 Installation:
- S5-Patch for original Step5
- PLCVCOM (virtual COM-Port)
Tools available on www.tpa-partner.de


Using S5-LAN++ with an ALF as a WLAN Router




- 1 Connect the 24V power source and the computer to configure



- 2 Select „AP-Router“ on menu „Easy Setup“



- 3 Configure your IP address and subnet mask



- 4 Now configure your networkname and encryption
Our recommended encryption is WPA2



- 5 Connect the S5-LAN++ with a patch cable
Your S5-LAN++ will get an IP from the DHCP server and is now available from every WLAN participants



- 6 Installation:
 - S5-Patch for original Step5
 - PLCVCOM (virtual COM-Port)Tools available on www.tpa-partner.de

Under the web-address <https://www.process-informatik.de> are product specific documentations or software-driver/-tools available to download.
If you have questions or suggestions about the product, please don't hesitate to contact us.

Process-Informatik Entwicklungsgesellschaft mbH

Im Gewerbegebiet 1

DE-73116 Wäschenbeuren

+49 (0) 7172-92666-0

info@process-informatik.de

<https://www.process-informatik.de>

Copyright by PI - 2026

Menutree Website:


- + Products / docu / downloads
- + Hardware
 - + Programming devices
 - + Programming adapter S7
 - + WLAN/WIFI
 - + Profinet PLCs / Ethernet-CPs
 - + ALF-Devices
 - + ALF

QR-Code Website:



Please make sure to update your drivers before using our products.

Data backup S5-PLC on USB-stick via dig. IO




Via digital input triggered DB-backup/-restore without additional PC via PG-socket and Ethernet to USB-stick

Analogue and ISDN - how do they come together?



You have on the plant side only ISDN for telephone, but in your office there is only an analogue system? No problem, you have to install on the clients side the TP-II and activate there the analogue-emulation in the device. No, the modem signals will be sent digitalized over ISDN and you can connect to it. So, you will be able to communicate though the telephone systems are different and your client isn't forced to install an analogue connection.

Fuzzy controller with the OSC-II




Through 3 free configurable limits (of each kind) you wont be able to realice a fuzzy-controller of your heat treatment furnace.

Data backup S7-PLC over MPI/Profibus on SD-card




S7-PLC triggered DB-backup/-restore without additional PC via MPI/Profibus on SD-card

Protection for data-dump and modification



You want to protect your system against unauthorized access and changes? No problem, with the S7-firewall you secure your system against unauthorized access and thus prevent deduction or alteration of your system and process data.

Communication with Win98 – XP/Vista/7/8/10/11 via network to S5-PLC



You still have a PC with Win98 and a MS-DOS-based Step5-package and would like to go Online on your S5-PLC via LAN? No problem, the provided virtual Com-Port PLCVCom emulates a COM-port on your PC with which you go Online. Even your MS-DOS-based Step5-software on this WIN98-PC can use this virtual Com-Port. With a patchtool for the Siemens Step5-software, which is provided as well, nothing else stands in your way to communicate via LAN.