


Technical data / connection
Magnetic base antenna for indoor use

Specification

Frequency range	2400 MHz – 2500 MHz
Gain	9.3 dBi
VSWR	$\leq 1.6:1$ Max.
Polarization	Linear, vertical
Impedance	50 Ω
Connector	R/P SMA PLUG

Environmental & Mechanical Characteristics

Temperature	-10°C to +55°C
Humidity	95% @55°C



Connection:

Place the antenna base on a metal surface and screw on the rod. Screw with feeling the cable on the device onto the WIFI socket.

Under the web-address <https://www.process-informatik.de> are product specific documentations or software-driver/-tools available to download.
If you have questions or suggestions about the product, please don't hesitate to contact us.

Process-Informatik Entwicklungsgesellschaft mbH

Im Gewerbegebiet 1

DE-73116 Wäschenbeuren

+49 (0) 7172-92666-0

info@process-informatik.de

<https://www.process-informatik.de>

Copyright by PI - 2025

Menutree Website:

+ Products / docu / downloads

+ Accessories

+ Antennas / Accessories

+ Magnetic base antenna for S5-/S7-BRIDGE / CONNECT

QR-Code Website:



Please make sure to update your drivers before using our products.

S5-PLC over USB



Communication with S5-PLC via USB, just how and with what?

Data-communication with S5-PLC from PC or other devices via USB, which interface is required. Questions you don't have to worry about. With "S5 over USB" you get the right interface-products for your interface of the PLC.

Which one you use then is up to you.

S7-PLC over WLAN/WIFI



Communication with S7-PLC via WLAN/WIFI, just how and with what?

Data-communication with S7-PLC from PC or other devices via WLAN/WIFI, which interface is required. Questions you don't have to worry about. With "S7 over WLAN/WIFI" you get the right interface-products for PPI, MPI and Profibus.

Which one you use then is up to you.

Remote maintenance with TS-software without original TS-adaptor



You have to reach urgend your PLC via remote maintenance and have no TS-adaptor in your company? No problem, configure with the MPI-Kabelmanager your S7-interface-cable MPI-II-Kabel the mode "TS" for "remote maintenance", connect this cable with the TS-Adapter (article number 9350-TS) with a standard modem and send it all to your client. Now you will be able to start the connection with your TS-software and solve the problem. And this all without buying a original TS-adapter.

Universally on machine and PLC



Remote access to all your systems, PLCs without great effort. Even triggering of actions by setting the integrated digital-outputs or reading in the digital and analog-inputs is possible via the Internet connection.

Regardless of whether you use your PC with the CONNECT-software or have connected a device from the CONNECT-family. Couplings via LTE also enable access to the LAN-interface on the system side. No special SIM-card is required for this.

A solution with little effort and everything within your "private" cloud.